

SUMMARY OF INTERNATIONAL AVOCADO IRRIGATION TRENDS

Simon Newett, DAF, April 2021

Thirteen very collaborative avocado experts from around the world kindly agreed to participate in this survey; five from California (four growers and one extension officer), two from Chile (both consultants), two from Israel (one extension officer and one consultant), one from New Zealand (a research manager), two from South Africa (both technical managers with large corporate producers), and one from Spain (a researcher). The aim was to find out trends in avocado producing countries outside of Australia in order to learn from others, identify common issues and identify where potential advances can possibly be made. This information will be shared with the Australian industry and international collaborators and will hopefully be useful to all.

A wealth of information was gathered however the information needs to be considered in the context of the growing conditions of the region being reported. Generally, where there was more than one respondent from one country, conditions were quite similar but there were differences in the environments of the two South African contributors.

Commonalities across all countries

In all countries surveyed irrigation is becoming a higher agronomic priority, reasons given are better yield and fruit size, more effective nutrition, and improved Phytophthora root rot management.

The biggest challenge across the board is the shortage of water.

Most countries believe that climate change is real and is generally resulting in drier and hotter conditions with more extreme weather events, especially heat waves.

CALIFORNIA

There were five respondents from California made up of one extension officer and four growers.

The climate is Mediterranean with rainfall ranging from 230 to 500mm/year, poorly distributed.

Soils range from sandy loams to clay loams with depth ranging from less than 30cm to more than 100cm.

100% of orchards are irrigated and 95% are fertigated. Phytophthora root rot is regarded by two respondents as a serious issue, one as a moderate issue and two as a minor issue. 5 to 33% of orchards are planted on mounds.

Irrigation water is very expensive, around AUD 1,000/ML (assuming an exchange rate of AUD 1.29 to US 1).

Water quality

Water quality is an issue, chloride content varies from 40 to over 150ppm. Measures taken to manage this issue are leaching irrigations, some chemistry, keeping soils wetter than would be necessary without salts, use of Dusa® and Toro Canyon root stocks, reverse osmosis, mounds, drip irrigation, humates, calcium sources, and changes in fertilisation methods and types.

Frequency of leaching is variable and ranges from every irrigation up to every fifth irrigation, monthly and six to eight times during the growing season. The frequency is determined by the

calendar, evapotranspiration (ETO), weather, soil and leaf tests, water quality and quantity available, rootstock, lysimeter and convenience.

One grower uses a leaf chloride over 0.25 to 0.35% as a trigger to leach, two others said that as leaf analysis is only done once per year it is not useful to determine leaching needs.

Current irrigation systems & practices

There has been a general trend towards more frequent light irrigations.

Annual irrigation volumes range from 6 - 12 ML/ha.

The period regarded as the most important to maintain optimum soil moisture is the entire cycle excluding autumn leaf flush and wintertime.

Mini sprinklers are the most commonly used system. Most growers use one sprinkler per tree delivering between 40 and 60 L/tree/hour, one uses 150 L/hr. Another grower uses two sprinklers per tree delivering a total of 58L/tree/hour. Two growers also use some drip irrigation. Configurations reported are two lines with emitters every 46 to 60 cm each delivering 1.6 or 4 L/emitter giving a total delivery rate per tree of 28 and 53 L/tree/hour respectively.

Two of the five respondents reported using overhead irrigation for the purpose of cooling the canopy. The range of soil depth growers aim to keep moist varies from 20 to 100cm. Irrigation is applied during the day and night. If a heat wave is forecast all growers will pre-irrigate deeper.

Monitoring devices

Most growers don't have weather stations on the farm.

Growers make irrigation decisions based on the calendar, ETO data supplied by the State or water company, physical examination of the soil using augers/spades. More recently growers have been adopting tensiometers, capacitance probes and gypsum blocks, driven by the high cost of water.

Where tensiometers are used the trigger point to irrigate ranges from 20 to 40 Cb depending on the time of year and stage of the phenological cycle.

Monitoring by devices is done remotely and automatically from continuously, to daily, to every four days. Where soil moisture is determined manually this is typically performed every two to three days.

Measures taken to make up for the fact that relatively tiny volumes of soil are measured by devices include using more than one method, physically examining the soil (with auger or spade), using the information from different areas, and observing the tree condition.

A few growers are using satellite images and a few are using Phytech dendrometers. The technology needs to be robust, easy to use and inexpensive if it is to be adopted.

Between 1 and 10% of growers are using software to amalgamate information from different sources to help with irrigation decisions.

Improving efficiency of water delivery

A wide range of answers ranging from 'very few', to 50% and 'most' are reported to clean their irrigation lines, and it is reported to be done from every second month to annually. Sulphuric acid,

phosphoric acid, and N-phuric (urea and sulphuric acid, used on alkaline soils) are being used for this purpose.

Between 25 and 80% of growers are trying to improve the root environment and this is being done with the use of mulch, humic acid and carbon based products.

Recent changes and the future

The biggest changes seen in avocado irrigation over the past 5 to 10 years include the fact that many growers have gone out of business due to high water costs which has gone up 10% a year for 10 years, and is now about AUD 1,000/ML. This has also impinged on the frequency of leaching irrigations. Other changes include greater use of ridges in combination with drippers and shorter but more frequent irrigations. There has also been more automation and more growers applying irrigation in anticipation of heat waves.

Expected changes in the next 5 – 10 years are that many will go out of business if water prices keep going up, more adoption of monitoring and better monitoring, more low flow/low pressure (dripper) irrigation, centralization of controls and fertigation, applying less water more often, and more automation.

The biggest challenge is the cost of water which is also declining in quality. Other challenges are drought and sudden heat waves.

Suggested research: can we irrigate the trees directly e.g. using an 'intra-venous' system instead of having to use the roots for water transfer? Cost efficient ways to improve water quality. Tailoring irrigation scheduling by soil type, cultivar and rootstock for each different region. One respondent said we know what to do we just need to achieve greater adoption of best practice.

Information required is chemistry that helps leach salts, grove specific information, on farm visits and one-on-one evaluations.

Factors considered critical in order to irrigate effectively are ETO information, correct understanding and utilization of resources available to help schedule irrigations, timing and quantity of water, and grower education.

One respondent stated that irrigation is just one of many things a grower does which include managing weeds, insects, disease, labour, regulations etc - it has to rise to top of priorities to get attention.

CHILE

Our two respondents are both consultants.

The growing area in Chile has a Mediterranean and semi-desert climate with quite cold winters. Avocados are generally grown on hill slopes (to avoid frost) in two different environments - coastal areas that have cooler but less variable temperatures (influenced by the cold Humboldt ocean current) and inland valleys which are drier and experience more extreme temperatures (hot and cold). Annual rainfall is poorly distributed and ranges from 150mm (inland valleys) to 300mm (coastal areas). The climate is reported becoming drier with up to 70% less rain.

The predominant soil type is clay loam and typical soil depth is from 30 to 100cm. 90 to 100% of trees are planted on mounds. 100% of orchards are irrigated and use fertigation. Phytophthora root rot is regarded as a minor issue.

Water quality

Water quality is an issue, chloride levels range from 20 to 80ppm.

Measures used to manage the poor water quality are monthly soil analysis, a leaching program, modifying irrigation frequency and using quality fertilizers.

Leaching is typically conducted once per month (using three times the regular volume of irrigation) over the five months of summer.

Leaching decisions are based on soil analysis (when chloride exceeds 2 meq/L), the soil moisture level and the calendar.

One respondent states that using leaf analysis to trigger leaching is always too late. The other respondent uses a leaf chloride level of 0.4% to trigger flushing.

Current irrigation systems & practices

There has been a trend towards more frequent, light irrigations.

Annual irrigation volumes range from 8 - 12 ML/ha.

The period regarded as the most important to maintain optimum soil moisture is for the entire crop cycle although one respondent does not regard winter as being quite as critical.

Both mini sprinklers and drip are used. A mini-sprinkler system typically uses one sprinkler per tree delivering 20 to 35 L/hr. Drip systems typically consist of three lines, the centre one on the sunny side of the trunk but never next to it, the other two placed 40 cm on either side of the central one. Some growers are changing to drip systems and some are changing to mini sprinkler. Overhead irrigation is not used to cool the canopy. Growers aim to keep the top 45 to 80cm of soil moist and apply irrigation during the day and night.

Monitoring devices

Growers have weather stations on site to help with irrigation decisions.

Growers use a combination of devices that include tensiometers, capacitance probes, excavating soil pits to examine soil moisture as well as root health and growth, use of ETO derived from weather station data and dendrometers on trees. All devices are regarded as being important. Capacitance probes are the most popular and allow continuous monitoring and the ability to evaluate water dynamics in the soil. Tensiometers are losing favour.

Monitoring is done remotely and automatically every 15 minutes to hourly.

One respondent reported that dendrometers can detect trunk size changes as little as 5 to 30 microns and are used to determine plant stress levels and daily growth rates which is combined with soil monitoring data to adjust irrigation timing, the number of pulse irrigations, and avoid plant stress. The other respondent reports that trunk measurement using dendrometers was tried several years ago but was a failure.

ETO is used to forecast irrigation needs for the next week.

Measures taken to make up for the fact that relatively tiny volumes of soil are measured by devices include ensuring that representative trees are used, digging soil pits, and using devices as indicators, not as 'gospel'. One respondent always uses three sensors per irrigation block.

One uses satellite, the other doesn't but all information from soil, tree and weather station goes to a central dashboard. 50 to 70% of growers are using software in this way to amalgamate information from different sources to help with irrigation decisions.

70% of growers are able to remotely view data from monitoring devices and control irrigation.

Improving efficiency of water delivery

All growers clean irrigation lines, this is considered a basic requirement. It is done with citric acid, chlorine dioxide, chlorine and /or phosphoric acid. Chlorine is used fortnightly or monthly and phosphoric acid is used every 2 months.

Between 10% to 80% of growers are reported to be trying to improve the root environment by using compost, mycorrhizae, humic acid and other organic matter.

Recent changes and the future

The biggest changes seen over the past 5 to 10 years have been better design of irrigation systems, better control of irrigation and soil moisture, and better maintenance of irrigation systems.

Expected changes in the next 5 – 10 years include improvements to valve design to allow more than 30 pulses per day, and better satellite and/or drone tools.

The biggest challenge is the shortage and quality of water.

One respondent believes that better execution and extension of existing knowledge is required instead of more research. The other believes that better sensors are required to make sure all trees receive the same amount of water, and that we need more reliable drone and/or satellite tools.

Good sensor readings and interpretation, a homogeneous irrigation system, and well maintained systems with a uniformity coefficient of above 95% are considered critical in order to irrigate effectively.

ISRAEL

Two respondents, one an extension officer with the Israeli department of agriculture and the other a consultant.

Israel has a Mediterranean climate (hot dry summers, cool wet winters) and experiences heat waves. Rain falls predominantly in winter, is fairly well distributed through winter and ranges from 650mm per year near the coast to 400mm in inland valleys. Both contributors feel that the climate is becoming hotter with more extreme weather events. Soils are clay loams and range from 60 to more than 100cm in depth, some trees are planted on mounds. 100% of orchards are irrigated and fertigated. Phytophthora root rot is absent or a minor issue.

Water quality

Water quality is a major issue with chloride levels over 150ppm. Measures being taken to manage this problem are the use of tolerant rootstocks and regular leaching.

Leaching varies from every 2 - 4 weeks, to twice during summer and at the start of winter rains.

Soil analysis & experience of the grower determines the frequency of flushing. Leaf analysis is not used for this purpose because when leaf chloride levels increase the damage is already there.

Current irrigation systems & practices

Irrigation frequency varies from 2-3 pulses per day, to daily, to every 2-3 days. It depends on soil type, ETO and other factors.

Annual irrigation volumes range from 6.5 - 8.5 ML/ha in coastal areas to 8 - 12 ML/ha inland.

The period regarded as the most important to maintain optimum soil moisture is the entire cycle although one respondent does not include flower initiation or winter as critical.

The main type of irrigation is drip. Typically, it consists of 2 lines, a dripper interval of 30-40 cm and emitter rates between 1.2 - 1.6 L/hr. This configuration delivers 26 to 32 L/tree/hr. The recent trend is towards emitter rates lower than 1 L/hr. One respondent reports the use of overhead irrigation for cooling purposes. Growers aim to keep the top 40cm of soil moist and will irrigate deeper if a heat wave is predicted. Irrigation is applied by day or night.

Monitoring devices

Growers have weather stations on site to help with irrigation decisions.

The main devices used to make irrigation decisions are tensiometers, augers/spades to physically examine soil moisture, ETO calculated by the Penman equation, and dendrometers. Dendrometers are reported to be better for spring and autumn, whilst tensiometers are best for summer.

One respondent gave the following irrigation trigger points for tensiometers: heavy soils 15-18 cB in summer and 30 cB in winter, light soils: 10-15 cB. The other gave the range as 25 - 35cB.

Monitoring is done remotely and automatically from hourly to daily.

Measures taken to make up for the fact that relatively tiny volumes of soil are measured by devices is to increase the number of monitoring sites, and to use Phytech technology.

Dendrometers on tree trunks are widely used. Continual monitoring is practiced, and the 'winning combination is the use of soil monitoring and tree monitoring together'. Dendrometers are useful for providing additional information for making decisions.

75 to 90% of growers can view soil moisture and control irrigation remotely. 75 to 90% of growers are also adopting software systems that bring together information from several sources.

Improving efficiency of water delivery

95 to 100% of growers clean their irrigation lines. Frequency depends on the quality of the water. The majority clean once a year, some twice a year. The most common product used is phosphoric acid, although some chlorine is used.

About 20% of growers are using measures including application of compost and humic acid to improve the root environment.

Recent changes and the future

The biggest changes seen over the past 5 to 10 years are better monitoring and the understanding that irrigation is the most important issue.

Expected changes in the next 5 – 10 years are less fresh water available, better quality recycled water (because more desalinated water will be available), a greater number of monitoring sites, and adjustment of irrigation protocols specific for each block.

The biggest challenges (and those that need to be researched) are how to irrigate during spring, selecting the correct volumes and intervals, and the optimum emitter rates for drippers.

Further development of dendrometer systems is seen as the key to making better irrigation decisions.

Factors considered critical in order to irrigate effectively are close monitoring of the soil and tree, and to know how much air the root system needs in spring after the winter rains.

NEW ZEALAND

The region reported on was Far North of the North Island where avocado farming is relatively new and conditions are sandier, warmer and drier and therefore irrigation more necessary than the more traditional growing region of the Bay of Plenty which is wetter and cooler with richer soils.

In the Far North the average annual rainfall is 1575mm and is well distributed with slightly more in winter. No drastic changes in climate are evident. The soil is a sand deeper than 100cm. Half the trees are planted on mounds, almost 100% are irrigated but only 20% are fertigated. Phytophthora root rot is a moderate issue.

Water quality

Water quality is not an issue.

Current irrigation systems & practices

Mini sprinklers are the dominant irrigation system and typically consists of one sprinkler per tree delivering about 75L/tree. Generally, growers try to keep the top 30cm of soil moist. Irrigation takes place at night. There is a trend for more frequent, light irrigations. Annual application is only about 2 ML/ha/yr. The phenological stages between bud burst through to mid-fruit growth are considered the most important for maintaining optimum soil moisture.

Monitoring devices

Capacitance probes are the most popular soil moisture monitoring device. The reasons given are that they are able to monitor continuously, their data can be accessed remotely, and they require less maintenance than tensiometers. Information is usually accessed daily. Where tensiometers are used 25cB is the trigger point on the shallow probe to start irrigating. Only about 10% of growers control their irrigation systems remotely but the number that are adopting software to amalgamate all available data to facilitate better irrigation systems is growing, currently also about 10%.

Measures taken to make up for the fact that relatively tiny volumes of soil are measured by devices is conducting soil surveys. Monitoring the tree itself is restricted to research on sap flow.

Improving efficiency of water delivery

97% of growers clean their irrigation lines annually. Phosphoric or sulphuric acid is used.

About 50% of growers are trying to improve the root environment by using mulch and biological soil amendments such as seaweed and humates.

Recent changes and the future

The biggest change in the past 5 – 10 years is that growers are now placing more trust in soil moisture monitoring devices.

Expected changes in the next 5 – 10 years are the use of more digital sensors and the availability of online data with recommendations.

Research suggested is a better understanding of negative impacts of moisture stress at different stages in the phenology.

Technology that would be useful is a platform that incorporates information from multiple sources such as weather forecasts and soil moisture devices to help with irrigation decisions.

Accurate soil moisture monitoring is considered critical in order to irrigate effectively.

SOUTH AFRICA

Two respondents one from a more benign environment near Tzaneen and other from a less benign environment near Nelspruit (Mbombela).

Both regions have predominantly summer rainfall and this ranges from 900 to 1000mm/year and it is generally not well distributed through the year. Soils range from clay in the Tzaneen area to sand in the Nelspruit region. 85 to 95% of orchards are irrigated. Most trees are not fertigated.

Phytophthora root rot is a moderate to serious issue.

Water quality

Water quality is not reported as becoming an issue although the orchards at Tzaneen practice longer irrigations every second week to leach salts.

Current irrigation systems & practices

There is a trend towards less frequent, heavier irrigations. Annual application is between 3 and 4 ML/ha/year. The period between budburst and early fruit growth is considered the most important period to maintain optimum soil moisture.

Irrigation is applied mainly through mini sprinklers. One or two sprinklers are used per tree to deliver between 30 (wetter) to 60 (drier areas) L/tree/hour. A little drip irrigation is used in drier areas, two lines are used per row with emitters 1m apart delivering between 0.7 and 1.6 L/hr/emitter so applying between 6 and 13 L/tree/hr. There is a trend towards more drip irrigation in new plantings especially as water becomes scarcer. Growers try and keep the top 40 to 60cm of soil moist. Irrigation is applied by day. One area irrigates deeper prior to heat waves.

Monitoring devices

Capacitance probes are the most popular devices because they are considered reliable, efficient, can be placed at different soil depths, save time and enable more precise irrigation management. Soil moisture is read remotely and automatically on a daily basis. However, tensiometers are also used because they give a clear indication of water potential in the soil 'if stress wants to be induced or prevented', 10 - 30cB is used as the irrigation trigger point depending on phenological stage.

Measures taken to make up for the fact that relatively tiny volumes of soil are monitored by devices include using more than one type of moisture monitoring device and increasing the number of monitoring sites.

One of the respondents notes that remote monitoring technology is becoming increasingly popular. Dendrometers are uncommon and are viewed by some as a research tool. They could be more effective if definite stress points within the phenology cycle could be identified. They need to be practical & easy to use for a grower, but they could provide more sensitive control during critical phenological stages.

80% of growers can view soil moisture status via a mobile device but only 5 - 20% can control the irrigation remotely.

Improving efficiency of water delivery

Only 10% of growers clean their irrigation lines.

Most growers try to improve the root environment. They use mulch, especially during establishment, organic fertilisers and additives. Sustainability is reported as a growing trend.

Recent changes and the future

The biggest changes seen over the past 5 to 10 years are better soil moisture monitoring, use of fertigation and more efficient irrigation systems e.g. drip.

Changes expected in the next 5 to 10 years include closer monitoring of soil moisture, logging data to simultaneously reduce orchard water use, more use of drip irrigation as water resources become scarcer, and automation to reduce costs.

Research suggested includes establishing crop factors suitable for different stages in phenology, and developing a drip irrigation design to suit different soil types. One respondent pointed out that we still don't know how much water avocado uses (and at different stages in the phenology).

Information that would help with better irrigation decisions include comparing results of monitoring both the tree and the soil, probes at different depths to read soil moisture and EC simultaneously and instantaneously, and accurate irrigation prediction models.

Factors considered critical in order to irrigate effectively are a good understanding of soil type and tree requirements (for different canopy sizes and phenological periods), truly understanding your soil type, monitoring soil moisture as much and as often as possible, and proper soil preparation (coupled with mounding) before planting to limit the effects of compaction etc that are often unseen.

SPAIN

Our respondent is a researcher based near Malaga.

Spain has a Mediterranean climate with an annual rainfall of about 485mm that is poorly distributed. More extreme weather events are reported as occurring together with milder winters.

The predominant soil type is clay loam and typical soil depth is 60 to 100cm. 50% of trees are planted on mounds. 100% of orchards are irrigated and 80% use fertigation. Phytophthora root rot is regarded as a moderate issue.

Water quality

Water quality is an issue, and the common chloride level is between 120-150ppm.

More tolerant rootstocks are the main measure to deal with this.

Current irrigation systems & practices

There has been a trend towards more frequent light irrigations.

Annual irrigation volume averages 6 ML/ha.

The period regarded as the most important to maintain optimum soil moisture is the entire cycle except for flower initiation and winter.

The main type of irrigation is drip. Typically, it consists of 3 lines, a dripper interval of 30 cm and emitter rates of 4 L/hr. This delivers between 160 to 213 L/tree/hr.

The recent trend is towards more drip irrigation. Overhead irrigation is used for cooling purposes. Growers aim to keep the top 40cm of soil moist and will irrigate deeper if a heat wave is predicted. The preferred time to irrigate is during the day

Monitoring devices

Growers have weather stations on site to help with irrigation decisions.

The main device used to make irrigation decisions is tensiometers which are regarded as easy to manage. The irrigation trigger points are between 20 - 30cB. Tensiometers are read every three days in the field.

The main measure taken to make up for the fact that relatively tiny volumes of soil are measured by devices is to increase the number of monitoring sites.

Dendrometers and sap flow meters are starting to be used but at this stage only for experimentation, however, monitoring the tree is regarded as being key in addition to soil monitoring. This will allow optimisation of irrigation applications specific to smaller groups of trees. It is believed that satellite imagery will become increasingly useful.

Only about 5% of growers view soil moisture and control irrigation remotely. As yet no growers are using software to amalgamate information from different sources to help with irrigation decisions.

Improving efficiency of water delivery

80% of growers clean their irrigation lines about once a year using phosphoric acid.

About 50% of growers are trying to improve the root environment and this is being done with the use of mulch.

Recent changes and the future

The biggest changes seen over the past 5 to 10 years is the change from mini sprinklers to drip irrigation.

Expected changes in the next 5 – 10 years are increasing use of drip ('low flow') irrigation and more use of satellite images.

The biggest challenge is the shortage of water.

Genetic research is needed to develop drought tolerant rootstocks.

The availability of appropriate and easy to use sensors is needed to measure soil and tree water status.

Factors considered critical in order to irrigate effectively are greater use of weather forecasts together with data from probes.

ACKNOWLEDGEMENTS

The project team would like to sincerely thank the 13 respondents who generously gave their time to complete the survey. The information has provided the project team and the industry valuable insights into the trends and issues amongst avocado irrigators around the world. It is expected that this information will be useful to all avocado producers.

This survey is part of the strategic levy investment project 'Avocado industry development and extension' AV17005. This project has been funded by Hort Innovation, using the Hort Innovation avocado research and development levy, co-investment from the Queensland Department of Agriculture and Fisheries, and contributions from the Australian government. Hort Innovation is the grower-owned, not-for-profit research and development corporation for Australian horticulture.

